

# SOUTH BEND 6 BURNER STOVE/OVEN



## INSTRUCTIONS

### OVEN LIGHTING:

#### STEP 1

Check that all knobs on the stove are in the "OFF" position (Red line pointing directly upwards).

#### STEP 2

Connect hose to propane tank. Once secured, turn valve on the propane tank to the "ON" position.

#### STEP 3

Open oven door and remove the heat shield located at the bottom of the oven to expose pilot light and burner.

#### STEP 4

Open bottom panel below oven door by lifting up on the panel. Once panel is open, locate the pilot knob. Turn knob to the "L PILOT" position and depress the button.

#### STEP 5

Light pilot while continuing to depress the button. Continue for 30 seconds then release the button, pilot should remain lit.

#### STEP 6

Turn pilot knob to the "ON" position.

#### STEP 7

Close the bottom panel and re-insert the heat shield. Turn oven dial to desired temperature.

### STOVE LIGHTING:

#### STEP 1

Check that all knobs on the stove are in the "OFF" position (Red line pointing directly upwards).

#### STEP 2

Connect hose to propane tank. Once secured, turn valve on the propane tank to the "ON" position.

#### STEP 3

Stove knobs correspond as follows: There are 3 sets of 2 knobs (right, middle and left). Each set is placed in front of their corresponding burners. The knob to the right of each set lights the **FRONT** burner.

#### STEP 4

With lighter in hand, turn stove knob to "10 o'clock" position and ignite the burner with the lighter.

#### STEP 5

Turn knob to desired flame height.



EVENT SOURCE  
PANACHE EVENTS

consistently delivering™

EVENT SOURCE  
EventSource.com  
877.901.0000

PANACHE EVENTS  
PanacheEvents.com  
800.30.PARTY (72789)

### AFTER HOURS

Call above toll free numbers and press Option 2. Please leave a message and we will respond shortly.

SKU 302-200 INCLUDES  
2 Shelves